

+44 (0)161 928 6221 info@hydratron.co.uk



## **TECHNICAL DATA SHEET**

GPU-GBD7/33-L\*\*/options PRODUCT SERIES **GPU- 2-Stage Double Acting** Air operated, high flow gas booster compressors offer a flexible and efficient source for delivering high pressure gases.



#### **FEATURES**

- Infinitely variable output pressure and flow
- Will hold static pressure without generating heat or consuming power
- Standard models are suitable for various gases
- Well proven and trouble-free operation
- Designed for ease of maintenance
- Low cost servicing
- Robust construction

#### **PERFORMANCE DATA**

| Max Rated Output Pressure                         | 5,700psi (393bar)                                   |
|---|---|
| Displacement Per Cycle                            | 35.8 in <sup>3</sup> (586cc)                        |
| Max Flow  | 6.94 scfm (196 NI/min)                              |
| Max Air Supply Pressure                           | 100psi (7bar)                                       |
| Ratio   | 60 : 1  |
| Air Consumption                                   | 120 scfm (3,400 NI/min)                             |
| Supply Pressure to Achieve Max Output<br>Pressure | 510psi (35bar)                                      |
| Actual Output Pressure (Stall Condition)          | 33 x (Air drive pressure) + 4.7 x (Supply pressure) |

#### **SEAL MATERIAL**

| Main Seals        | MoS2  |
|-------------------|-------|
| Check Valve Seals | Viton |







Pag. 2 of 3

### **CONSTRUCTION**

| Frame            | Stainless Steel  |
|------------------|--|
| Air Motor        | Anodised Aluminium / Nitrile (Buna-N) Seals  |
| Gas Cylinder     | 17-4PH   |
| Piston           | Aluminum Bronze / 17-4PH + Chrome Finish   |
| Check Valves     | Stainless Steel  |
| Pilot Air Valves | Brass / Stainless Steel Internals / Nitrile (Buna-N) Seals / Stainless<br>Steel Silencer |
| L1** (standard)  | Brass / Copper Gas Inlet, Air Inlet and Plated Steel Silencer                            |
| L2** (optional)  | Stainless Steel Gas Inlet, Air Inlet and Silencer  |

### CONNECTIONS

| Gas Inlet  | 1/2" NPT(F)   |
|------------|---------------|
| Gas Outlet | 1/4" NPT(F)   |
| Air Inlet  | 3/4" BSPP(F)  |
| Net Weight | 100kg (220lb) |

# **COMMON OPTIONS (BUT NOT LIMITED TO)**

| / A                             | ATEX (94/9/EC) II 2GD c T5   |
|---------------------------------|--|
| / F                             | Panel mount digital stroke counter (non ATEX)  |
| / G                             | Panel mount pneumatic stroke counter   |
| / I (over all dimension varies) | Isolation valve  |
| / K                             | Inlet gas gauge  |
| / M                             | Mild steel painted frame (Painted Blue) + Stainless steel tank (if applicable to the unit) |
| / O (over all dimension varies) | Single pen chart recorder complete with recorder isolation valve                           |
| / R                             | Relief valve   |
| / W                             | Fitted with wheels   |
| / X                             | Gauge protection guard   |
|                                 |  |







#### **GENERAL LAYOUT DRAWING**

#### Model: PU-PU-GBD7/33



